

4721

VHF P25 Mobile Radio



General Properties

- Analog and Digital Mode
- Appropriate to P25 Standard
- User Notifications and Alerts
- LCD Screen
- Alphanumeric Keypad
- Graphical User Interface
- Call Log
- Caller ID
- 3 Level RF Power Level
- Channel Search
- Sending Time Limit
- Menu Authorization
- Computer Aided Repair
- Show and Send Location Via External GPS
- Appropriate to MIL-STD-810C/D/E/F/G Standards
- Appropriate to TIA-102.CAAB-D and TIA-603-D standards

Digital Mode Properties

- Group Call
- Individual Call
- Emergency Call
- SMS (Radio to Radio)
- Data Communication (with data software pack)
- Status Message
- Encryption (Optional)
- Phone Book
- Call Alert

Standards

IEC 61149	MIL-STD-810C/D/E/F/G
ETSI EN 300 086-2	TTTE Directive
ETSI EN 300 113-2	TIA-102.CAAB-D
ETSI EN 301 489-1,5	TIA-603-D
ETSI EN 60950	



4721

VHF P25 Mobile Radio

General Technical Specifications

Modulation	Analog FM, C4FM (P25)
Channel Range	12,5 / 25 kHz (Analog) 12,5 kHz (P25)
Data Speed (Digital)	9,6 kb/s
Voice Encoder	4,4 kb/s IMBE
Encryption Algorithms	DES-OFB, AES
Channel Numbers	999
Power Supply	13,6 Vdc \pm 20%
Screen	64 x 128 pixel LCD
Keypad	20 key (backlit)
Dimensions (HxWxD)	46 x 165 x 165 mm (except borders)
Weight	1,50 kg
Operation Temperature	-30°C / +60°C
Storage Temperature	-40°C / +85°C
Humidity	95% @ 50°C

Receiver Technical Specifications

Frequency Range	136-174 MHz
Audio Output Power*	7,5 W / 8 Ω
Sensitivity	
TIA 12dB SINAD / %5BER**	$\leq 0,25\mu\text{V}$
ETSI 20dB SINAD / %1BER	$\leq 0,35\mu\text{V}$
Intermodulation Rejection*	$\geq 75\text{dB}$
Spurious Response Rejection*	$\geq 80\text{ dB}$
Receiver Noise Ratio	
25 kHz Channel	$\geq 48\text{ dB}$
12,5 kHz Channel	$\geq 42\text{ dB}$
Audio Distortion*	$\leq 3\%$

Transmitter Technical Specifications

RF Output Voltage *	10-40 W
Frequency Accuracy * (-30°C / +60°C; 25°C ref)	$\pm 2,5\text{ ppm}$
Modulation Limitation *	
25 kHz channel	$\pm 5,0\text{ kHz}$
12,5 kHz channel	$\pm 2,5\text{ kHz}$
Transmitted Spurious Broadcasting*	$\leq -20\text{ dBm}$

* Values are measured in analog mode in accordance with EIA-603 under normal conditions.

** Values are measured in digital mode in accordance with TIA 102-CAAA under normal conditions.

aselsan

Communication and Information Technologies

T: (312) 592 10 00 F: (312) 354 13 02

www.aselsan.com.tr

hbtmarketing@aselsan.com.tr